



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ :

A61M 5/24, 5 /28

A1

(11) International Publication Number:

WO 00/02605

(43) International Publication Date:

20 January 2000 (20.01.00)

(21) International Application Number: PCT/DK99/00386

(22) International Filing Date: 5 July 1999 (05.07.99)

(30) Priority Data:

PA 1998 00909 8 July 1998 (08.07.98) DK
PA 1998 01500 17 November 1998 (17.11.98) DK

(71) Applicant: NOVO NORDISK A/S [DK/DK]; Novo Allé, DK-2880 Bagsværd (DK).

(72) Inventors: BUCH-RASMUSSEN, Thomas; Dalvej 28, DK-2820 Gentofte (DK). MUNK, Benny; Bæverskov Allé 52, DK-2720 Vanløse (DK). POULSEN, Jens-Ulrik; Virumgade 54 C, DK-2830 Virum (DK). LJUNGREEN, Henrik; Jonstrupvej 244 A, DK-2750 Ballerup (DK). JENSEN, Peter, Møller; Svenstrupvej 6, DK-2970 Hørsholm (DK). JENSEN, Jens, Møller; Nyhavn 37, DK-1051 Copenhagen K (DK).

(74) Agent: HØIBERG APS; Nørre Farimagsgade 37, DK-1364 Copenhagen K (DK).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: A MEDICAL DELIVERY DEVICE AND A CARTRIDGE ASSEMBLY FOR USE IN THE SAME

(57) Abstract

The present invention relates to a medication delivery device comprising a cartridge assembly, a dosing assembly and optionally a needle assembly. The cartridge assembly comprises a cartridge having a stopper adapted to receive a plunger means. Furthermore, the cartridge assembly has one end sealed with a pierceable sealing, said end comprising coupling means for engaging a needle assembly, and another end comprising coupling means for engaging the dosing assembly. At least one of the coupling means of the cartridge assembly is unitarily moulded with the cartridge. The dosing assembly comprises a plunger means and has coupling means for engaging the cartridge assembly. The cartridge assembly and the dosing assembly are coupled together for delivering selected doses of medication. The cartridge is preferably moulded from a plastic material, such as a transparent material, and may be housed in a cartridge housing for protection of the cartridge. The coupling means may be selected from threaded locks, snap locks, hinged locks, or bayonet locks. The medication delivery device is especially suitable for delivering insulin, growth hormone or the like medicines.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

A MEDICAL DELIVERY DEVICE AND A CARTRIDGE ASSEMBLY FOR USE IN THE SAME

The present invention relates to a medication delivery device having a cartridge and a dosing assembly coupled together for delivering selected doses of medication, wherein at least one of the coupling means of the cartridge is unitarily moulded with the cartridge.

Background

Some medication, such as insulin is self-administered. The typical diabetes patient will require injections of insulin several times during the day. The required insulin dose will vary from patient to patient, and will for each patient often also vary during the day. Each patient will often establish a regimen for the insulin administration adjusted to his or her insulin need as well as lifestyle. Medication delivery pens have been developed to facilitate the self-administration of medication, such as insulin.

One prior art medication delivery pen includes a pen body assembly comprising a medication cartridge and a plunger device. A needle assembly may be connected to the pen body assembly. The medication is delivered by moving or pressing a plunger in the direction of the needle assembly thereby delivering the medication. When the medication in the cartridge is exhausted the pen body assembly is discarded. Depending on the medication needs for each individual the medication in the cartridge will last for several days. During this period the needle assembly will often have to be displaced by a new assembly or new needle due to increasing bluntness of the needle making injections painful for the patient.

More recent developments have revealed medication delivery pens, wherein the cartridge holder assembly can be disassembled from the pen body assembly after the medication therein has been exhausted, discarded and replaced by a new medicine-containing cartridge assembly.

An example of this is shown in EP 0 688 571 disclosing a medication delivery pen having a reusable pen body assembly and a disposable cartridge assembly that are threadably engageable with one another. The cartridge assembly comprises a cartridge, a cartridge housing, a cap between the distal end of the cartridge and the housing; securing the cartridge in the housing and being adapted for engagement

with a needle assembly. Furthermore, the cartridge comprises a plunger within the cartridge. The reusable pen body assembly is coupled through a threaded coupling to the cartridge housing. Thus, the total number of parts comprising the prior art cartridge assembly is high.

5

It is an object of the present invention to provide a medication delivery device wherein the amount of parts of the cartridge is minimised.

Summary of the invention

10

Accordingly, the present invention relates to a medication delivery device comprising a cartridge assembly, a dosing assembly and optionally a needle assembly,

15

said cartridge assembly having one end sealed with a pierceable sealing, said end of the cartridge assembly comprising coupling means for engaging a needle assembly, and another end comprising coupling means for engaging the dosing assembly, said cartridge assembly further comprising a cartridge wherein at least one of the coupling means of said cartridge assembly is unitarily moulded with the cartridge, the cartridge further comprising a stopper adapted to receive plunger means, and

20

said dosing assembly comprising plunger means has coupling means for engaging the cartridge assembly, and said plunger means is adapted to engage the stopper of the cartridge when the dosing assembly is coupled to the cartridge.

25

30

The unitarily moulded coupling(s) secure(s) that the coupling is not accidentally released from the cartridge during use and storage. Also, the above-described medication delivery device has fewer parts than the prior art devices because at least one coupling means is moulded unitarily with the cartridge. Thereby the costs involved in the production and assembling of the device are reduced, and the device is more economical, which is an important feature for a disposable device.

The medical delivering device may either be manufactured as a disposable device which is sold pre-filled with the insulin or it may appear as a durable medical delivering device so designed that it can receive disposable cartridges with insulin.

5

In a preferred embodiment the dosing assembly is reusable and the cartridge assembly is disposable, and accordingly, a second aspect of the present invention is a medication delivery device wherein the dosing assembly is releasably coupled to the cartridge assembly.

10

The medication delivery device is preferably constructed as to secure that the plunger means abuts on the stopper during use of the device, such as attaching and releasing the needle assembly. It is understood that the plunger means must disengage the stopper when the cartridge assembly is deliberately released from a reusable dosing assembly because the medication in the cartridge has been exhausted and the cartridge assembly is to be discarded. In this situation the plunger means is to be retracted to the dosing assembly before assembling the device with a new cartridge assembly.

15

20

Securing the abutment of the plunger means on the stopper during use of the medication delivery device, in particular when the needle assembly is coupled to and/or decoupled from the cartridge assembly, may be carried out by a variety of means. In a preferred embodiment the abutment is secured by preventing the cartridge assembly from being inadvertently released from the dosing assembly.

25

30

In particular, when the cartridge assembly is released from the dosing assembly through a movement including an axial movement, such as through a threaded coupling, it is preferred that the means for releasably coupling the needle assembly and the cartridge assembly together are such that the coupling and/or decoupling of the needle assembly cannot cause an axial movement of the cartridge assembly with respect to the dosing assembly. Thus, in that respect examples of the preferred couplings between the needle assembly and the cartridge assembly include releasable snap locks. Another preferred embodiment includes a safety on the coupling between the dosing assembly and the cartridge assembly, such as hinge on the

coupling or a threaded coupling releasable only after exerting an axial pressure on the coupling.

5 A second aspect of the present invention is a cartridge assembly for use in a medication delivery device, said cartridge assembly having one end sealed with a pierceable sealing, said end of the cartridge assembly comprising coupling means for engaging a needle assembly, and another end comprising coupling means for engaging the dosing assembly, said cartridge assembly further comprising a cartridge wherein at least one of the coupling means of said cartridge assembly is unitarily
10 moulded with the cartridge, said cartridge further comprising a stopper.

The cartridge assembly may further comprise a cartridge housing for protecting the cartridge in use. Furthermore, when the cartridge is moulded unitarily with one coupling means the cartridge housing may comprise the other coupling means. According-
15 accordingly, in one embodiment of the invention the housing of the cartridge assembly comprises coupling means for coupling the cartridge assembly to the dosing assembly, preferably the coupling means is moulded unitarily with the housing. The cartridge is arranged within the cartridge housing. The cartridge housing may be non-releasably attached to the cartridge, once the cartridge is arranged in the
20 housing, whereby the housing is disposed with the cartridge. In another embodiment the housing is reusable and the cartridge is arranged releasably in the housing.

In a preferred embodiment all the coupling means of the cartridge assembly are unitarily moulded with the cartridge. Thereby, it is possible to construct the cartridge
25 assembly without the housing providing a cartridge assembly with even fewer parts.

The coupling means of the cartridge assembly may be for any suitable coupling, preferably a releasable coupling. Examples of the coupling are snap locks, such as snap locks with guidewire and sideways snap locks, snap locks released through
30 threads, bajonet locks, luer locks, hinged locks, threaded locks and any suitable combinations thereof.

The coupling means unitarily moulded with the cartridge are preferably external coupling means, such as an external threaded coupling.

In particular the coupling means for engaging to the dosing means may be an external threaded coupling.

5 The cartridge may be moulded from any material suitable for medical containers. The cartridge is preferably moulded from a plastic material, e.g. by injection moulding. A suitable choice of material allows the cartridge to be at least partly transparent, whereby the user can see whether content, such as liquid is left in the cartridge. In a preferred embodiment the cartridge is totally transparent giving the user a
10 greater possibility of inspecting the content of the cartridge.

By using a plastic material as compared to the usual glass material a great advantage is achieved in the production lines. Normally a significant quantity of the produced glass cartridges will be spoiled in the lines due to breakage, however the loss
15 is greatly reduced by the use of plastic cartridges. Furthermore, the risk of small loose glass particles in the cartridges have been eliminated.

Also, by moulding the coupling(s) unitarily with the cartridge a very precise coupling mechanism may be obtained, since no further steps are to be taken to attach coupling means to the cartridge.
20

The cartridge may be of any suitable form, such as a cylinder. The cylinder may be constructed with various combinations of circular or non-circular inner and outer cross-section. In another embodiment the cartridge may be box-shaped having essentially rectangular or triangular cross-section.
25

The stopper is in sliding fluid tight engagement in the cartridge. The stopper is preferably made of plastic and/or rubber material.

30 The flexibility of the cartridge wall is not critical, however if the cartridge is too flexible the function of the stopper may be impaired. Mostly, the cartridge is made of a material only slightly flexible to non-flexible.

In order to enforce and strengthen the cartridge wall the cartridge may be integrally moulded with reinforcements. Thereby, the necessity of a protective housing may be obviated. Furthermore, a scale may be integrally moulded with the cartridge wall providing the user with a measure for the medication used and left.

5

In a most preferred embodiment the cartridge assembly is comprised only of a cartridge being sealed in one end with a sealing, being unitarily moulded with all couplings means and comprising a stopper.

10

In a cylindrical cartridge the two couplings of the cartridge assembly are generally opposing each other having the same axis. However, the coupling for engaging with the dosing assembly being separate from coupling for engaging the needle assembly may be arranged so that their axis are in any angle with respect to each other, such as perpendicular, or even parallel, but not overlapping.

15

Another aspect of the present invention is a cartridge being at least partly filled with liquid medication, such as insulin.

20

In another embodiment the invention relates to a medication delivery device for transferring medication from the cartridge into a syringe with a needle. In this embodiment the coupling means for engaging the needle assembly may be replaced by coupling means for engaging the syringe, or coupling means for both may be provided. The coupling means may be a syringe holder, for example a cylinder coupled to the cartridge comprising a central bore for receiving the syringe. The syringe is coupled to the cartridge having the needle piercing the sealing. By activation of the dosing means the metered amount of medication is driven into the syringe. The syringe is then ready for injection after being removed from the cartridge.

25

Drawings

30

Fig. 1 is an exploded perspective view of the medication delivery device.

35

Fig. 2 is a cross-sectional view showing part of the medication delivery device, 2a immediately after assembling before the first injection, and 2b after some time of use.

Fig. 3 is a cross-sectional view showing the cartridge before assembling of the medication delivery device.

5 Detailed description of the invention

A medication delivery device in accordance with the present invention is identified generally by the numeral 20 in Fig. 1 and 2. Medication delivery device 20 includes a dosing assembly 6, and cartridge assembly 1, a needle assembly 16 and a cap 10 14.

The dosing assembly 6 is illustrated in Fig. 1 and 2. It is understood, however, that the dosing assembly 6 according to the invention may be any suitable dosing unit including plunger means, and accordingly, that variations from the depicted embodiment may be provided, and are considered to be within the scope of this invention. In the depicted embodiment the dosing assembly 6 includes a cylindrical housing surrounding the plunger means 17 of the dosing unit and having opposed proximal and distal ends.

In one aspect of the invention the plunger means comprises a rod element 7 which is adapted to engage the stopper 4 of the cartridge assembly 1. The rod element 7 advances axially into the cartridge 5 during injections. The dosing assembly may have any suitable driving means for advancing the rod element 7.

The dosing unit 6 preferably also comprises scale means 10 indicating the dosing quantity selected by activating the dose setting means 9 for defining specified selected doses of medication to be delivered. The selected dose may be delivered by actuating the actuator button 18. The actuator button is part of the driving means of the dosing assembly exerting its force on the rod element 7.

The dosing assembly further comprises coupling means 8 adapted for engagement with the cartridge assembly. The coupling means 8 may be internal or external couplings. In a preferred embodiment the coupling 8 is an internal coupling.

The cartridge assembly 1 is illustrated in Fig. 1 and 2, and in greater detail in Fig. 3. In Fig. 1 cartridge assembly 1 includes a moulded cartridge 5 extending from proximal end 21 to distal end 22.

5 At the distal end 22 of the cartridge assembly 1 is provided coupling means 2 for releasably mounting a needle assembly 11. At the proximal end 21 of the cartridge assembly 1 is provided coupling means 3 for mounting a dosing assembly 6. The coupling means are as described above.

10 Cartridge 5 also comprises a stopper 4 in sliding fluid tight engagement within said cartridge 5. The stopper 4 is adapted to receive the plunger means, such as a rod element 7 of the dosing assembly 6. The rod element 7 is adapted to exert an axial movement of the stopper 4 towards the sealed end 22 of the cartridge 5.

15 The cartridge assembly 1 may further comprise a housing for protecting some or all of the cartridge 5. When the cartridge assembly 1 includes a housing, one of the couplings 2, 3 of the cartridge may be moulded unitarily with the housing.

20 Instead of the protective housing the cartridge 5 may have integrally moulded reinforcements of the cartridge wall.

The depicted cartridge 5 is cylindrical having couplings 2, 3 at opposed ends. However, the cartridge may obtain any suitable form and the cross-section may be circular or non-circular, such as substantially triangular or oval.

25 The device according to the invention may include a protective cap 14 that is removably mounted over the cartridge assembly 1 and/or the needle 11 and which is removed before injection of the medication in the cartridge 5. The cap further ensures that the content of the cartridge is protected against sunlight.

30 Referring to Fig. 3 the coupling means of the cartridge are shown in greater detail. The coupling means 3 is an external thread, whereas the coupling means 2 is a recess for a snap lock of the needle assembly. Both coupling means are moulded unitarily with the cartridge.

The various parts of the medication delivery device are advantageously made of plastics, e.g. by injection moulding.

- 5 The medication delivery device 20 may further comprise any appropriate needle assembly 11, such as a double ended needle 13 having opposed proximal and distal points and a lumen extending axially therebetween.

10 A mounting hub 12 is engaged on the needle 13 and is removably connected to the coupling means 2 at the needle end of the cartridge assembly. The relative location of the mounting hub 12 ensures that the proximal point of the needle 13 will pierce the sealing when the mounting hub 12 is engaged with the coupling means 2 on the cartridge assembly 1.

- 15 The needle assembly 11 may further comprise a removable shield or cap 15 for protecting against accidental needle sticks.

20 The device according to the invention is suitable for delivering pre-set dosages of insulin, it is however understood that the device is suitable for the injection of pre-set dosages of other liquids.

In use the user will set the dose by means of the dose setting means 9. Before activating the actuator button 18 the cap 14 must be removed from the cartridge assembly 1 whereby the device 20 is prepared for an injection. The injection is effected by activating the actuator button 18, which again will effect the stopper 4 to be moved towards the sealed end 22 of the cartridge 5, thereby delivering the desired pre-set dosage. A subsequent dosage of medication will be set in exactly the same manner as described above. However, for such a subsequent dosage, the rod element 7 and the stopper 4 will be in a partly advanced position as starting point.

30 Dose setting and injections can be carried out until all of the medication has been used.

Claims:

- 5 1. A medication delivery device comprising a cartridge assembly, a dosing assembly and optionally a needle assembly,

10 said cartridge assembly having one end sealed with a pierceable sealing, said end of the cartridge assembly comprising coupling means for engaging a needle assembly, and another end comprising coupling means for engaging the dosing assembly, said cartridge assembly further comprising a cartridge wherein at least one of the coupling means of said cartridge assembly is unitarily moulded with the cartridge, the cartridge further comprising a stopper adapted to receive plunger means, and

15 said dosing assembly comprising plunger means having coupling means for engaging the cartridge, and said plunger means is adapted to engage the stopper of the cartridge when the dosing assembly is coupled to the cartridge.

- 20 2. A medication delivery device according to claim 1, wherein all the coupling means of the cartridge assembly are unitarily moulded with the cartridge.

3. A medication delivery device according to claim 1 or 2, wherein at least one coupling means of the cartridge is an external coupling.

25 4. A medication delivery device according to any of the preceding claims, wherein at least one coupling means of the cartridge is a threaded coupling.

5. A medication delivery device according to claim 4, wherein the coupling means for engaging to dosing means is an external threaded coupling.

30

6. A medication delivery device according to any of the preceding claims, wherein the cartridge is moulded of a plastic material.

7. A medication delivery device according to any of the preceding claims, wherein the cartridge is at least partly transparent.
8. A medication delivery device according to any of the preceding claims, wherein
5 reinforcements of the cartridge wall are integrally moulded with the cartridge.
9. A medication delivery device according to any of the preceding claims, wherein the cartridge further comprises a cartridge housing.
10. A medication delivery device according to any of the preceding claims, wherein
10 the cartridge further comprise a scale.
11. A medication delivery device according to any of the preceding claims, wherein the cross-section of the cartridge is non-circular.
12. A medication delivery device according to any of the preceding claims, wherein
15 the coupling means of the cartridge are opposed each other.
13. A cartridge assembly for use in a medication delivery device, said cartridge assembly having one end sealed with a pierceable sealing, said end of the cartridge assembly comprising coupling means for engaging a needle assembly,
20 and another end comprising coupling means for engaging the dosing assembly, said cartridge assembly further comprising a cartridge wherein at least one of the coupling means of said cartridge assembly is unitarily moulded with the cartridge,
25 said cartridge further comprising a stopper.
14. A cartridge assembly according to claim 13, wherein all the coupling means of the cartridge are unitarily moulded with the cartridge.
15. A cartridge assembly according to claim 13 or 14, wherein at least one coupling
30 means of the cartridge is an external coupling.
16. A cartridge assembly according to any of the claims 13-15, wherein at least one coupling means of the cartridge is a threaded coupling.

17. A cartridge assembly according to claim 16, wherein the coupling means for engaging to dosing means is an external threaded coupling.
- 5 18. A cartridge assembly according to any of the claims 13-17, wherein the cartridge is moulded of a plastic material.
19. A cartridge assembly according to any of the preceding 13-18, wherein the cartridge is at least partly transparent.
- 10 20. A cartridge assembly according to any of the claims 13-19, wherein reinforcements of the cartridge wall are integrally moulded with the cartridge.
21. A cartridge assembly according to any of the claims 13-20, wherein the cartridge further comprises a cartridge housing.
- 15 22. A cartridge assembly according to any of the claims 13-21, wherein the cartridge further comprise a scale.
- 20 23. A cartridge assembly according to any of the claims 13-22, wherein the cross-section of the cartridge is non-circular.
24. A cartridge assembly according to any of the claims 13-23, wherein the coupling means of the cartridge are opposed each other.
- 25 25. A cartridge assembly according to any of the claims 13-24, which is filled with medicine.


$\frac{1}{2}$ 

Fig. 1

2/2




Fig. 2 a




Fig. 2 b




Fig. 3

INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 99/00386

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: A61M 5/24, A61M 5/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC, WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0688571 A1 (BECTON DICKINSON AND COMPANY), 27 December 1995 (27.12.95), figures 7-11 --	1-25
A	US 4936833 A (B. SAMS), 26 June 1990 (26.06.90), figures 2,3 --	1-25
A	US 5226895 A (D.C. HARRIS), 13 July 1993 (13.07.93), figure 1 --	1-25
A	US 5549575 A (L. GIAMBATTISTA ET AL), 27 August 1996 (27.08.96), figure 1 --	1-25

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

9 December 1999

Date of mailing of the international search report

20-12-1999

Name and mailing address of the ISA:

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Johan Löfstedt / MR

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 99/00386

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5688251 A (L.H. CHANOCH), 18 November 1997 (18.11.97), figure 4 -- -----	1-25

INTERNATIONAL SEARCH REPORT

Information on patent family members

02/11/99

International application No.

PCT/DK 99/00386

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0688571 A1	27/12/95	CA 2151702 A	23/12/95
		JP 2689372 B	10/12/97
		JP 8000730 A	09/01/96
		US 5725508 A	10/03/98
		US 5827232 A	27/10/98
US 4936833 A	26/06/90	AT 70195 T	15/12/91
		AU 598679 B	28/06/90
		AU 1747088 A	15/12/88
		DE 3866790 A	23/01/92
		DK 170141 B	06/06/95
		DK 312388 A	13/12/88
		EP 0295075 A,B	14/12/88
		FI 882771 A	13/12/88
		JP 63318952 A	27/12/88
		NZ 224861 A	26/04/90
		US 4865591 A	12/09/89
US 5226895 A	13/07/93	US 5308340 A	03/05/94
US 5549575 A	27/08/96	CA 2156696 A	14/03/96
		DE 69507920 D,T	19/08/99
		EP 0701832 A,B	20/03/96
		ES 2130537 T	01/07/99
		JP 8098886 A	16/04/96
US 5688251 A	18/11/97	CA 2231868 A	27/03/97
		EP 0862473 A	09/09/98
		WO 9710864 A	27/03/97

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)